



4000 SERIES:

CHARGE AIR CONNECTOR HOSE AND CLAMP KITS



Flexfab's 4000 series CAC hose and clamp kits feature 4-ply silicone coated meta-aramid fabric with stainless steel pressure retention rings. They perform well in extreme temperatures and have all stainless steel spring-loaded T-bolt clamps. The clamps resist salt water and can be used in marine applications.

APPLICATION:

+ Flexfab 4000 series clamp kits provide a CAC hose and 2 spring-loaded T-bolt clamps with each kit. Hoses provided in these kits are compatible with both hot or cold side of the charge air cooler system.

CONSTRUCTION:

+ Charge air connector hose, 4-ply silicone coated meta-aramid fabric with stainless steel pressure retention rings
+ All stainless steel spring-loaded T-bolt clamps

SPECIFICATIONS:

+ Charge air connector wall thickness is .085"/.135"
+ Spring-loaded T-bolt clamps: resists salt water and may be used in marine applications

BENEFITS

- ✓ Extreme Temperature Resistance
- ✓ Extreme Duty Cycle Tested for Hostile Engine Environments
- ✓ High Pressure Resistance
- ✓ Salt Water Resistant Clamps

CUSTOM ENGINEERED TO WITHSTAND:



COOL TEMPS



HOT TEMPS



OIL SPLASH
RESISTANCE




OZONE
RESISTANT



DIRECT
SUNLIGHT

TEMPERATURE RANGE:



4000 SERIES: CHARGE AIR CONNECTOR HOSE AND CLAMP KITS

Part Number	Hose and Clamp Provided in Kit	Inside Diameter		Outside Diameter		Overall Length Inches	Convulutes (Humps)	Stainless Steel Rings	Max Operating Pressure - PSI
		Inch	MM	Inch	MM				
KIT4001D	4070-0001	4.00	102	4.23	107	6.00	2	3	70
	FLX2588-0406	4.06	103	4.38	111	N/A	N/A	N/A	N/A
KIT4002D	4070-0002	4.00	102	4.23	107	6.00	2	3	70
	FLX2588-0406	4.06	103	4.38	111	N/A	N/A	N/A	N/A
KIT4003D	7727-0001	4.00	102	4.23	107	8.00	2	3	50
	FLX2588-0406	4.06	103	4.38	111	N/A	N/A	N/A	N/A
KIT4004D	4073-0001	3.50	89	3.73	95	6.00	2	3	70
	FLX2588-0356	3.56	91	3.88	98	N/A	N/A	N/A	N/A
KIT4005D	4074-0001	3.00	76	3.23	82	6.00	2	3	70
	FLX2588-0306	3.06	78	3.38	86	N/A	N/A	N/A	N/A

*Specifications for reference only. Specific test data available on request.