



# HEAVY-WALL CHARGE AIR CONNECTOR (CAC)

## FLUOROCARBON LINED



### FLUOROCARBON LINED CHARGE AIR CONNECTOR

These connectors have a fluorocarbon liner that the other heavy wall hoses don't have. They're designed to meet EPA 2007 and EURO IV & V reduced emissions requirements.

#### CONSTRUCTION:

- + High temperature fluorocarbon elastomeric liner
- + 4-ply heavy duty silicone coated meta-aramid fabric with heavy duty stainless steel pressure retention rings

#### SPECIFICATIONS:

- + Wall thickness is .117"/.163"

### BENEFITS

- ✓ Extreme Temperature Resistance
- ✓ Extreme Duty Cycle Tested for Hostile Engine Environments
- ✓ Custom Design
- ✓ Clamp Saddle Design Allows for Proper Clamp Alignment
- ✓ Chamfered ID is Easy to Install

#### CUSTOM ENGINEERED TO WITHSTAND:



COOL TEMPS



HOT TEMPS



OIL SPLASH  
RESISTANCE




OZONE  
RESISTANT



DIRECT  
SUNLIGHT

#### TEMPERATURE RANGE:





## FLUOROCARBON LINED CHARGE AIR CONNECTOR

Part Number	Inside Diameter		Outside Diameter		Overall Length Inches	Convolute (Humps)	Stainless Steel Rings	Max Operating Pressure - PSI	Weight LBS	Clamp
	Inch	MM	Inch	MM						
1076-0003	2.50	64	2.73	69	6.00	2	3	80	0.5	2583-0250
1074-0003	3.00	76	3.23	82	6.00	2	3	70	0.5	2588-0306
1073-0003	3.50	89	3.73	95	6.00	2	3	70	0.5	2588-0356
1070-0003	4.00	102	4.23	107	6.00	2	3	70	0.5	2588-0406
1075-0003	4.50	114	4.73	120	6.00	2	3	60	0.5	2588-0456

\*Specifications for reference only. Specific test data available on request.